# **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number: WO 96/18383
A61K 7/50, 7/48	A1	(43) International Publication Date: 20 June 1996 (20.06.96)
(21) International Application Number: PCT/US (22) International Filing Date: 15 December 1994 (		DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(71) Applicant: ALBEMARLE CORPORATION [US/0] Florida Street, Baton Rouge, LA 70801-1780 (US)		Published  With international search report.
(72) Inventors: CHANG, Suae-Chen; 12515 N. Oak Hills Baton Rouge, LA 70810 (US). CORONA, Raynold General Mouton Avenue, Baton Rouge, LA 70810	, J.; 181	
(74) Agent: PIPPENGER, Philip, M.; Albemarle Corpora Floride Street, Baton Rouge, LA 70801-1780 (US)		1

#### (54) Title: STABLE WATER-IN-SYNTHETIC HYDROCARBON FLUID EMULSIONS

#### (57) Abstract

Freeze-thaw stable water-in-oil emulsions include: an external phase comprising a polyalphaolefin fluid; an internal aqueous phase which contains a polyglyveryl fatty acid diester type non-ionic emulsifier having a HLB value of less than about 5, a non-ionic emulsifier having a HLB value of above about 8 and, optionally, an ethoxylated vegetable oil type non-ionic emulsifier having a HLB value of less than about 5, and an emulsion stabilizer.

# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IB	Ireland	NZ	New Zealand
B.J	Benin	п	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
a	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	u	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spein	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	Prance	MN	Mongolia	VN	Viet Nam
GA	Gabon		-		

## STABLE WATER-IN-SYNTHETIC HYDROCARBON FLUID EMULSIONS

This invention relates generally to water-in-oil type emulsions and more particularly to stable, high water content, water-in-oil type emulsions having alpha-olefin oligomer fluids such as polydecene fluids as the continuous phase, which can be formed at ambient temperatures.

5

10

15

20

25

Alpha-olefin oligomer fluids, often referred to in the art as "polyalphaolefins", have been used to replace mineral oils in a number of applications including personal care products such as lotions and creams. Cosmetic products containing polyalphaolefin fluids are described, for example, in published Japanese patent applications SHO (1977) - 72832 and SHO (1978) - 27772.

High water content water-in-oil emulsions are desirable from the standpoint of cost, less oily feel, and an enhanced cooling effect ("freshness") due to evaporation of the larger amount of water. A problem associated with high water content, water-in-oil emulsions made from alphaolefin oligomer fluids, such as the commercially available polydecenes, is emulsion stability, especially when the products are subjected to several freeze-thaw cycles.

Preeze-thaw stable, long shelf life water-in-oil emulsions using alpha-olefin oligomer fluids have now been provided by using certain combinations of non-ionic emulsifiers. The emulsions can be formed at ambient temperatures, which saves energy.

In accordance with this invention there is provided a freeze-thaw stable water-in-oil emulsion composition comprising:

an external phase comprising a polyalphaolefin fluid;

an internal aqueous phase;

5

10

15

20

25

a non-ionic emulsifier system consisting essentially of a polyglyceryl fatty acid diester type non-ionic emulsifier having a HLB value of less than about 5, a non-ionic emulsifier having a HLB value of from about 8 to 10 and, optionally, an ethoxylated vegetable oil non-ionic emulsifier having a HLB value of less than about 5; and

an emulsion stabilizer.

Polyalphaolefin fluids are hydrogenated, branched chain liquids which are prepared by oligomerizing alphaolefins which have from about 6 to 20 and, preferably, 8 to 14 carbon atoms. Preferred polyalphaolefins for use in the emulsion compositions of the invention have kinematic viscosities at 100°C of from about 2 to 20 cSt and especially preferred are polydecenes having viscosities of from about 2 to 12 cSt. These fluids constitute the external or continuous phase and in cosmetic applications act as an emollient. The fluids are, preferably, present in amounts of from about 5 to 40 and, more preferably, from about 9 to 25 weight percent of the emulsion compositions. The water is preferably present in the range of from about 50 to 85

weight percent of the emulsion compositions and more preferably from about 65 to 75 weight percent.

5

10

15

20

25

The non-ionic emulsifier system includes a polyglyceryl fatty acid diester type non-ionic emulsifier which has a HLB value of less than about 5.0 and preferably from about 4.0 to 4.9. Non-limiting examples include triglyceryl dioleate, diglyceryl dipalmitate and the like. Preferred are branched alkyl chain esters such as triglyceryldiisostearate. The emulsifier system also includes a non-ionic emulsifier which has a HLB value of from about 8 to 10. Preferred are polyoxyethylene sorbitan esters of fatty acids such as PEG (40) sorbitol septaoleate. The system can also include an ethoxylated vegetable oil type non-ionic emulsifier which has a HLB value of less than about 5 and preferably from about 4.0 to 4.9 such as PEG-7 hydrogenated castor oil.

The amounts of the emulsifier components are chosen to provide a combined HLB value of from about 5 to 7 depending upon the emulsifier system used and, preferably in a two-component system, about 5.9 for polydecenes, which value has been found to provide freeze-thaw and storage stable polydecene containing water-in-oil emulsions. The combined HLB value is a straight line relationship which can be readily calculated by multiplying the proportion of each emulsifier in the system by its HLB value and adding up the resulting values, as is known in the art. Although emulsifiers having HLB values above 10 will provide the required HLB value for the system, They do not provide stable emulsions. Likewise, the use of a vegetable oil

type emulsifier in a two component emulsifier system does not provide a stable emulsion. In general, the total amount of emulsifiers in the emulsion compositions will range from about 2 to 10 weight percent and, preferably, from about 4 to 7 weight percent.

The emulsions also contain from about 0.1 to 0.5 weight percent an emulsion stabilizer. Preferred are inorganic acid salts. Non-limiting examples of such inorganic salts include alkali metal salts, alkaline earth metal salts and aluminum salts of inorganic acids such as hydrochloric acid, sulfuric acid and nitric acid. Preferred inorganic salts include potassium sulfate, magnesium sulfate, potassium chloride, magnesium chloride and aluminum chloride. Other types of stabilizers, such as fatty acid salts could be used.

The emulsions can be used in a variety of applications such as drilling fluids and health care products such as pharmaceutical and cosmetic creams and lotions. The health care product emulsions will include one or more appropriate ingredients selected from emollients, preservatives, humectants, fragrances, thickeners, moisturizers, antifoam agents, opacifiers, colorants, covering agents, and active agents such as pharmaceuticals (antibiotics, antiseptics, antifungals, antihistamines, analgesics, etc.) vitamins, sunscreens, insect repellents, deodorants, antiperspirants, cleaning agents, moisturizers, and the like. Normally the total amount of these additive ingredients will not exceed about 10 wt. percent of the total emulsion composition.

- 4 -

20

15

5

10

25

The emulsions can be made by mechanical mixing techniques as known in the art at ambient temperatures, e.g. about 20 to 30°C.

The invention is further illustrated by, but is not intended to be limited to, the following examples wherein parts are parts-by-weight unless otherwise indicated.

### Example 1

5

10

15

20

A stable water-in-oil emulsion is prepared at room temperature using the following ingredients:

Ingredient	<u>Function</u>	Amount
Part A		
PEG-7 Hydrogenated Castor Oil	Emulsifier	1.7
(HLB 4.7)		
Triglyceryl-3-Diisostearate ) (HLB 4.7	Emulsifier	2.7
POE (40)-Sorbitol Septaoleate	Emulsifier	2.5
(HLB 9.5)		
Vitamin E	<b>Vitamin</b>	5.0
Polydecene (4 cSt at 100°C)	Emollient	16.6
Part B		
Glycerin	Humectant	3.0
Magnesium Sulfate	Stabilizer	0.3
Water	Diluent	67.2

### Part C

5

10

Propylene Glycol & Diazolidinyl Preservative 1.0
Urea & Methylparaben & Polyparaben

The emulsifier system has a HLB value of about 6.4. The emulsion is prepared by adding Part B to Part A with mixing at 25-30°C until a uniform mixture is obtained (about 1 hour). Part C is then added with mixing to provide a lotion. The emulsion is stable through three freeze-thaw cycles and oven aging of 45°C for over one month. The vitamin E helps to provide a stable emulsion.

#### Example 2

A stable water-in-oil emulsion is prepared at room temperature using the following formulation.

	Ingredient	<u>Function</u>	Amount
15	Part A		
	Triglyceryl-3-Diisostearate	Emulsifier	5.2
	POE (40) - Sorbitol Septaoleate	Emulsifier	1.7
	Polydecene (4 cSt at 100°C)	Emollient	21.6
	Part B		
20	Glycerin	Humectant	3.0
	Magnesium Sulfate	Stabilizer	0.3
	Water	Diluent	68.2

The emulsifier system (6.9 weight percent surfactants) has a HLB of about 5.9. The emulsion is prepared by adding Part B to Part A with mixing at room temperature (25 to 30°C) until a uniform mixture is obtained. The mixture is then homogenized for three minutes. The water-in-oil emulsion is stable through three freeze thaw cycles and oven aging for one month.

#### Example 3

5

10

15

20

A stable water-in-oil emulsion is prepared at room temperature using the following formulation:

Ingredient	Amount
Part A	
PEG-7 hydrogenated Castor oil	1.95
Triglyceryl diisostearate	3.25
POE (40)-sorbitol septaoleate	1.7
Polydecene (2 cSt at 100°C)	21.6
Part B	
Glycerin	3.0
MgSO₄	0.3
Water	68.2

#### Example 4

Stable water-in-oil emulsions are formed using the same ingredients and process as in Example 2 except that 3.8 parts of triglyceryl-3-diisostearate, 1.2 part of

- 7 -

POE (40)-sorbitol septaoleate and 23.5 parts of polydecene (5.0 weight percent surfactants) are used.

#### Example 5

5

10

15

20

Stable water-in-oil emulsions are formed using the same ingredients and process as in Example 2 except that 3.0 parts of triglyceryl-3-diisostearate, 1.0 part of POE (40)-sorbitol septaoleate, and 24.5 parts polydecene (4.0 weight percent surfactants) are used.

The advantages of the above emulsions include:

- (1) Stability these emulsions are stable after three freeze-thaw cycles and oven aging at 45°C for over one month.
  - (2) Silky Feel the polydecene-containing lotion gives silkier, less greasy feel than mineral oil-containing ones.
  - (3) Energy Saving Since these emulsions were prepared at room temperature it saves energy to prepare them.
- (4) Low Cost These emulsions can employ a large internal aqueous phase and still be freeze-thaw stable.

# Comparison 1

A water-in-oil emulsion is prepared using the formulation as in Example 2, except that 5.2 parts of triglyceryl-3-diisostearate is replaced by 5.2 parts of PEG-7 hydrogenated castor oil. The resulting emulsion is not stable.

#### Comparison 2

5

10

A water-in-oil emulsion is prepared as in Example 2 except that the emulsifier system (6.9 weight percent surfactants HLB 5.9) is 6.1 parts of Span 60 sorbitan monoester or stearic acid (HLB 4.7) and 0.8 parts of Tween 60 POE derivative of sorbitan mono-ester of stearic acid (HLB 14.9). The emulsion is not stable.

### Comparison 3

A water-in-oil emulsion is prepared as in Example 2 except that emulsifier system (6.9 weight percent surfactants HLB 5.9) is 5.98 parts of Brij 72 stearyl alcohol ethoxylate (HLB 4.9) and 0.92 part of Brig 76 stearyl alcohol ethoxylate (HLB 12.4). The emulsion is not stable.

What Is Claimed Is:

5

10

15

20

1. A freeze-thaw stable water-in-oil emulsion composition comprising:

an external phase comprising a polyalphaolefin fluid;

an internal aqueous phase;

a non-ionic emulsifier system consisting essentially of a polyglyceryl fatty acid diester type non-ionic emulsifier having a HLB value of less than about 5, a non-ionic emulsifier having a HLB value of from about 8 to 10 and, optionally, an ethoxylated vegetable oil type non-ionic emulsifier having a HLB value of less than about 5; and

an emulsion stabilizer.

- 2. The composition of claim 1 wherein said poly-alphaolefin fluid is derived from an  $\alpha$ -olefin monomer having from 8 to 14 carbon atoms and has a kinematic viscosity of from about 2 to 12 cSt at 100°.
  - 3. The composition of claim 2 wherein said poly- alphaolefin fluid is polydecene.
  - 4. The composition of claim 3 wherein said emulsifier system has a HLB value of from about 5 to 7, and said emulsion stabilizer is magnesium sulfate.

5. The composition of claim 1 which includes at least one agent selected from the group consisting of fragrances, pharmaceutical compounds, sunscreens, insect repellents, vitamins, antiperspirants, cleaning agents, moisturizers, and deodorants.

5

10

15

20

25

- 6. The composition of claim 1 wherein said emulsifier system consists essentially of a polyglyceryl fatty acid diester type non-ionic emulsifier having a HLB value less than about 5 and a non-ionic emulsifier having a HBL of from about 8 to 10.
- 7. The composition of claim 6 wherein the polyalphaolefin fluid is polydecene and the HLB value of the emulsifier system is about 5.9.
- 8. The composition of claim 1 wherein the amount of polyalphaolefin fluid is from about 5 to 40 weight percent of the emulsion composition and the amount of water is from about 50 to 85 weight percent of the emulsion composition.
- 9. The composition of claim 1 which includes said ethoxylated vegetable oil type non-ionic emulsifier.
- 10. A freeze-thaw stable water-in-oil emulsion composition comprising:

an external phase which comprises a polydecene fluid having a kinetic viscosity of from about 2 to 4 cSt at 100°C, said fluid making up from about 9 to 25 weight percent of said composition;

an external aqueous phase the water in said aqueous pahse making up from about 65 to 75 weight percent of said composition;

a non-ionic emulsifier system consisting essentially of triglyceryl disostearate and POE (40) - Sorbitol septaoleate in proportions to provide a combined HLB value of about 5.9; and

magnesium sulfate.

5

10

15

20

11. A freeze-thaw stable water-in-oil emulsion composition comprising:

an external phase which comprises a polydecene fluid having a kinetic viscosity of from about 2 to 4 cSt at 100°C, said fluid making up from about 9 to 25 weight percent of said composition;

an external aqueous phase the water in said aqueous phase making up from about 65 to 75 weight percent of said composition;

a non-ionic emulsifier system consisting essentially of triglyceryl dissostearate, POE (40) - Sorbitol septaoleate, and PEG-7 hydrogenated castor oil in proportions to provide a combined HLB value of about 6.4;

vitamin E; and

magnesium sulfate.

# INTERNATIONAL SEARCH REPORT.

Intern. sal Application No PCT/US 94/14417

	TOTAL TONI OF SUBTROP 14 A TOTAL		
A. CLASSI IPC 6	ification of subject matter A61K7/50 A61K7/48		
According to	to International Patent Classification (IPC) or to both national classifi	cation and IPC	
	S SEARCHED		
Minimum d	locumentation searched (classification system followed by classification	on symbols)	
IPC 6			
Documenta	iron searched other than minimum documentation to the extent that s	uch documents are included in the fields s	erched
Electronic d	data base consulted during the international search (name of data base	and, where practical, search terms used)	
C. DOCUM	MENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the re-	evant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 15 no. 392 (C-0873) ,4 Octob & JP,A,O3 161417 (KANEBO LTD) see abstract	er 1991	1
٨	EP,A,O 422 862 (RICHARDSON-VICKS April 1991 see the whole document	INC.) 17	1
٨	WO,A,94 27574 (L'OREAL) 8 Decembe see the whole document	r 1994	1
٨	EP,A,O 336 900 (WARNER-LAMBERT CO October 1989 see the whole document	MPANY) 11	1
	-	·/	
X Fur	other documents are listed in the continuation of box C.	X Patent family members are listed	in annex.
* Special co		To later document published after the int or priority date and not in conflict w cited to understand the principle or to invention	IN INC SUBSICING OUR OUT
E' carlier	r document but published on or after the international clate the international clate ment which may throw doubts on priority claim(s) or	"X" document of particular relevance; the cannot be considered novel or canno involve an inventive step when the di	coment is taken alone
which citation	nent which the stablish the publication date of another on or other special reason (as specified) ment referring to an oral disclosure, use, exhibition or	"Y" document of particular relevance; the cannot be considered to involve an it document is combined with one or of ments, such combination being obvice	claimed invention eventive step when the tore other such docu-
other "P" docum	means	ments, such commination being cover in the art.  *&* document member of the same paten	
1	e actual completion of the international search	Date of mailing of the international a 2 6. 09. 95	earch report
	13 September 1995	-	
Name and	mailing address of the ISA  European Patent Office, P.B. 5818 Patentiaan 2  NL - 2280 HV Rijswik	Authorized officer	
	Tel. (+ 31-70) 340-2040, Tr. 31 651 epo nl. Fax: (+ 31-70) 340-3016	Couckuyt, P	

1

# INTERNATIONAL SEARCH REPORT

tnern. .sal Application No PCT/US 94/14417

C.(Continu	ALCO) DOCUMENTS CONSIDERED TO BE RELEVANT	Relevant to claim No.
tegory *	Citation of document, with indication, where appropriate, of the relevant passages	Control to Come 140.
\	EP,A,O 408 965 (KAO CORPORATION) 23 January 1991 see the whole document	1
A	DATABASE WPI Week 9213	1
	Derwent Publications Ltd., London, GB; AN 92-101987 & JP,A,04 045 842 (MITSUBISHI HEAVY IND	
	KK), 14 February 1992 see abstract	
A	DATABASE WPI Week 7703 Derwent Publications Ltd., London, GB;	1
	AN 77-04582y & JP,A,51 138 735 (MISUI PETROCHEM KK) , 1 December 1976	
	see abstract	
	·	
Ì		
1		
1		
1		

### INTERNATIONAL SEARCH REPORT

information on patent family members

Intern. .atl Application No PCT/US 94/14417

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP-A-422862	17-04-91	US-A- AU-B- AU-A- CA-A, C CN-A- JP-A- TR-A-	5011681 626466 6397390 2026963 1051671 3169804 25525	30-04-91 30-07-92 18-04-91 12-04-91 29-05-91 23-07-91 01-05-93
WO-A-9427574	08-12-94	FR-A- AU-B-	2705891 6931594	09-12-94 20-12-94
EP-A-336900	11-10-89	US-A- AU-B- JP-A- PT-B-	4992476 3232589 2015021 90198	12-02-91 05-10-89 18-01-90 30-06-94
EP-A-408965	23-01-91	JP-A- JP-B- US-A-	3050299 7008991 5154850	04-03-91 01-02-95 13-10-92